(19) World Intellectual Property **Organization**

International Bureau





(43) International Publication Date 23 June 2005 (23.06.2005)

PCT

(10) International Publication Number WO 2005/056208 A1

(51) International Patent Classification⁷: B21D 13/00, 13/02

(21) International Application Number:

PCT/RU2003/000551

(22) International Filing Date:

11 December 2003 (11.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English


- (71) Applicants (for all designated States except US): OTKRYTOE AKTSIONERNOE OBSCHESTVO "KAZANSKY NAUCHNO-ISLEDOVATELSKY IN-STITUT AVIATSIONNOI TEKHNOLOGII" [RU/RU]; ul. Dementieva, 2v, Kazan, 420036 (RU). "AIRBUS" [FR/FR]; 1 Rond Point Maurice Bellonte, F-31707 Blagnac Cedex (FR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): AKISHEV, Niaz Irekovich [RU/RU]; ul. Kulahmetova, 18-209, Kazan,

420033 (RU). ZAKIROV, Ildus Muhametgaleevich [RU/RU]; ul. Vishnevskogo, 10-24, Kazan, 420043 (RU). NIKITIN, Alexandr Vladimirovich [RU/RU]; ul. S.Halturina, 11/10-60, Kazan, 420032 (RU).

- (74) Agent: VOSTRIKOV, Gennadi Fedorovich; Leningradsky pr., 47-3-215, Moscow, 125167 (RU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DEVICE FOR SHEET MATERIAL CORRUGATION



(57) Abstract: The invention can be defined in its most general form as a device for sheet material corrugation by means of bending and can be used in production of light core for sandwich panels, and elements of heat-exchange apparatus. The device includes the pivotedly connected in-between shaping and auxiliary systems of dies (4) and the drive for their transformation including the system of vacuumization and the chamber (3) made of flexible gas-proof material where the latter of said systems is fixed. Used to set the system of shaping dies (4) into its initial plane state is the mechanism made in the form of rigid chamber with the perforated cap (2) providing the possibility to connect the chamber to the system of vacuumization. The device also includes the subsidiary flexible removable vacuum chamber (8) wherein the blank (6) from sheet material is placed in contact with the shaping system of dies (4). Said chamber and the transformation drive chamber have a common wall rigidly connected to the shaping and auxiliary systems of dies (4) at locations of their pivot connection.



Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.